

C211K/060060PSF

Pressed Steel Access Cover, 600mm x 600mm clear opening, 25mm depth, Loading code K



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	625 x 625	25	Pedestrian

4

KEY FEATURES

- Hot dipped galvanised for corrosion resistance.
- Covers are supplied with built in concealed lifting handles for cover removal without the need for manhole keys or tools.
- Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code C211K/060060PSF

Primary material Steel

Category Access cover

Flanges

Gross laden vehicle weight 2.5 tn

Load duty Pedestrian

Seal type Single seal





Standards, classes and groupings

Wrekin loading code K

Dimensions

Frame shape Rectangular

Overall top of frame (A x B) 625 mm x 625 mm

Clear opening (C x D) 600 mm x 600 mm

Frame depth (E) 25mm

Base opening (F x G)

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our Terms and Conditions of Sale







