

C236N/228071/BT

Recessed cover for block paving, 2285mm x 710mm clear opening, 86mm frame depth, Wrekin loading code N, BT Approved



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
2,285 x 710	2,360 x 783	86	

KEY FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Can be installed by a single person, providing labour cost savings.

SPECIFICATION

General information

Stock code	C236N/228071/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	6
Chamber ref	10

Standards, classes and groupings

BS EN 124 Class	B125
Wrekin loading code	N

Dimensions

Frame shape	Rectangular
Overall top of frame (A x B)	783 mm x 2,360 mm
Clear opening (C x D)	2,285 mm x 710 mm
Frame depth (E)	86mm
Base opening (F x G)	
Overall base of frame	870 mm x 2,445 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

