

## DGH0D4/3633/KT

Tristar D400 3 flange gully grate 360mm x 335mm clear opening with 100mm frame depth



RANGE	CLEAR OPENING (MM)	BASE OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	WATERWAY AREA (CM²)	OPTIONS
Tristar	360 x 335	380 x 355	505 x 425	100	750	<input type="checkbox"/> Screw locking

## KEY FEATURES

- ✓ Captive hinges reduce theft risk whilst allowing easy lifting.

## SPECIFICATION

### General information

Stock code	DGH0D4/3633/KT
Primary material	Ductile iron
Range	Tristar
Category	Gully grate
Flanges	3

### Standards, classes and groupings

Standards	BS EN 124-2 CD 526 (formerly HA 102/17)
BS EN 124 Class	D400
BS EN 124 Group	3

	4
Third party certified	Kitemark
CD 526 hydraulic capacity	S

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	505 mm x 425 mm
Clear opening (C x D)	360 mm x 335 mm
Frame depth (E)	100mm
Base opening (F x G)	380 mm x 355 mm
Waterway area	750cm <sup>2</sup>

## AVAILABLE OPTIONS

### ✓ Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak <sup>®</sup> rapid curing polyester resin mortar

STOCK CODE	DESCRIPTION
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

## NOTES

The D400 load capability of these Group 3 products also offers the benefit of making them suitable for exposure to Group 4 traffic types. Where 3-flange D400 Gully Grate assemblies are employed, we recommend that they are installed against a kerb, not in an open highway location. All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

