

C291X/060045

Steel Block Paviour Access Cover, 600mm x 450mm clear opening, 100mm tray depth, Loading code X



| CLEAR OPENING (MM) | OVERALL TOP OF FRAME (MM) | FRAME DEPTH (MM) | LOAD DUTY |
|-----------------------|------------------------------|---------------------|------------|
| 600 x 450 | 665 x 515 | 105 | Heavy duty |

KEY FEATURES

✓ Hot dipped galvanised for corrosion resistance.

✓ Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

| | |
|--|--------------|
| Stock code | C291X/060045 |
| Primary material | Steel |
| Category | Access cover |
| Flanges | 4 |
| Gross laden vehicle weight | 44 tn |
| Load duty | Heavy duty |
| Slow moving wheel load (pneumatic tyres) | 11.5 |

Standards, classes and groupings

Wrekin loading code X

Dimensions

| | |
|------------------------------|-----------------|
| Frame shape | Rectangular |
| Manhole shape | Rectangular |
| Overall top of frame (A x B) | 515 mm x 665 mm |
| Clear opening (C x D) | 600 mm x 450 mm |
| Frame depth (E) | 105mm |
| Base opening (F x G) | |
| Overall base of frame | 600 mm x 665 mm |

ACCESSORIES

| STOCK CODE | DESCRIPTION |
|------------|--|
| KEYSHEAVY | Large cover lifting keys with a standard handle (sold as a pair) |

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)



