


C291X/060060

Steel Block Paviour Access Cover, 600mm x 600mm clear opening, 100mm tray depth, Loading code X



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	665 x 665	105	Heavy duty

KEY FEATURES

→ Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code C291X/060060

Primary material Steel

Category Access cover

Flanges 4

Gross laden vehicle weight 44 tn

Load duty Heavy duty

Slow moving wheel load (pneumatic tyres) 11.5





Standards, classes and groupings

Wrekin loading code X

Dimensions

Frame shape Rectangular

Manhole shape Rectangular

Overall top of frame (A x B) 665 mm x 665 mm

Clear opening (C x D) 600 mm x 600 mm

Frame depth (E) 105mm

Base opening (F x G)

Overall base of frame 740 mm x 665 mm

ACCESSORIES

STOCK CODE	DESCRIPTION
KEYSHEAVY	Large cover lifting keys with a standard handle (sold as a pair)

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>

















