

## C291M/060060/D4

Steel Block Paviour Access Cover, double seal, 600mm x 600mm clear opening, 100mm tray depth, Loading code M

| CLEAR OPENING (MM) | OVERALL TOP OF FRAME (MM) | FRAME DEPTH (MM) | LOAD DUTY           |
|--------------------|---------------------------|------------------|---------------------|
| 600 x 600          | 655 x 655                 | 132              | Light / medium duty |

### **KEY FEATURES**

→ Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

# **SPECIFICATION**

#### **General information**

**Stock code** C291M/060060/D4

Primary material Steel

**Category** Access cover

Flanges 4

Gross laden vehicle weight 10 tn

Light / medium duty

Slow moving wheel load (pneumatic tyres) 2.5

Seal type Double seal





## Standards, classes and groupings

Wrekin loading code M

**Dimensions** 

Frame shape Rectangular

Manhole shape Rectangular

Overall top of frame (A x B) 655 mm x 655 mm

Clear opening (C x D) 600 mm x 600 mm

Frame depth (E) 132mm

Base opening (F x G)

Overall base of frame 735 mm x 655 mm

#### **ACCESSORIES**

| STOCK CODE | DESCRIPTION  |
|------------|--|
| KEYSHEAVY  | Large cover lifting keys with a standard handle (sold as a pair) |

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>

















