

PMS1M2/30D

Safeseal A15 polypropylene manhole cover 300mm diameter clear opening with 40mm frame depth



RANGE	OVERALL FRAME (MM)	CLEAR OPENING (MM)	FRAME DEPTH (MM)	OPTIONS
Safeseal		Ø 300	40	<input type="checkbox"/> Neoprene seal <input type="checkbox"/> Ventilation holes

KEY FEATURES

- ✓ Labyrinth seal helps to prevent odour escapes and water ingress.

SPECIFICATION

General information

Stock code	PMS1M2/30D
Primary material	Plastic
Range	Safeseal
Category	Manhole cover
Flanges	4

Standards, classes and groupings

Standards	BS EN 124-2
-----------	-------------

Dimensions

Frame shape	Circular
Manhole shape	Circular
Clear opening (C x D)	Ø 300 mm
Frame depth (E)	40mm
Base opening (F x G)	

AVAILABLE OPTIONS

✓ Neoprene seal

A neoprene seal can be included to reduce ingress and egress of dirt and gasses from the chamber.

✓ Ventilation holes

Provide additional cover ventilation in addition to the product's natural ventilation, up to the BS EN 124 allowance.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

