

FasTrack 609®

FasTrack 609 Woven Geotextile, 1500N, 75g/m² - 4.5m x 100m roll (mini packs and folded rolls also available)



DESCRIPTION

FasTrack 609 Woven Geotextile, 1500N, 75g/m² - 4.5m x 100m roll (mini packs and folded rolls also available)

SPECIFICATION

General information

Stock code	GTSG/FASTRACK/609
Range	FasTrack
Third party certified	UKCA CE
Roll sizes	4.5m x 100m 5.25m x 100m
Geotextile product range	FasTrack

Geotextile properties

Material	Polypropylene
Tensile strength (MD)	EN ISO 10319 18kN/m
Tensile strength (CMD)	EN ISO 10319 10kN/m
Elongation at max load (MD)	EN ISO 10319 25%
Elongation at max load (CMD)	EN ISO 10319 25%
Dynamic perforation resistance	EN ISO 13433 19mm

CBR puncture resistance	EN ISO 12236	1500N
Dynamic cone drop	EN ISO 13433	19mm
Water permeability	EN ISO 11058	16L/m ² .s
Characteristic opening size	EN ISO 12956	300µm
Weight	EN ISO 9864	75g/m ²

NOTES

Folded rolls available. Folded for convenient transport, easily fits in a van.

Mini pack roll sizes also available:

Stock code	Mini pack roll size
GTSG/FAST/1X14A	1m x 14m
GTSG/FAST/4.5X11A	4.5m x 11m
GTSG/FAST/2.25X25A	2.25m x 25m
GTSG/FAST/2.25X50A	2.25m x 50m

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

