

MultiTrack NW 16

MultiTrack NW 16 Nonwoven Geotextile, 2400N, 200g/m² - 5.25m x 100m roll



DESCRIPTION

MultiTrack NW 16 Nonwoven Geotextile, 2400N, 200g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTNW/16
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	16kN/m
Tensile strength (CMD)	EN ISO 10319	16kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	19mm
CBR puncture resistance	EN ISO 12236	2400N
Dynamic cone drop	EN ISO 13433	19mm

Water permeability	EN ISO 11058	85L/m ² .s
Characteristic opening size	EN ISO 12956	85µm
Thickness under 2kPa	EN ISO 9863-1	1.25mm
Weight	EN ISO 9864	200g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

