

MultiTrack SNW 17

MultiTrack SNW 17 Superior Nonwoven Geotextile, 1700N, 150g/m² - 4m x 100m roll



DESCRIPTION

MultiTrack SNW 17 Superior Nonwoven Geotextile, 1700N, 150g/m² - 4m x 100m roll

SPECIFICATION

General information

Stock code	GTSNW/17
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	4m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	10.3kN/m
Tensile strength (CMD)	EN ISO 10319	10.3kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	60%
Dynamic perforation resistance	EN ISO 13433	22mm
CBR puncture resistance	EN ISO 12236	1700N
Dynamic cone drop	EN ISO 13433	22mm

Water permeability	EN ISO 11058	100L/m ² .s
Characteristic opening size	EN ISO 12956	110µm
Thickness under 2kPa	EN ISO 9863-1	1.5mm
Weight	EN ISO 9864	150g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

