

## MultiTrack SNW 120

MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N, 1000g/m<sup>2</sup> - 5.25m x 35m roll



### DESCRIPTION

MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N, 1000g/m<sup>2</sup> - 5.25m x 35m roll

## SPECIFICATION

### General information

|                          |            |
|--------------------------|------------|
| Stock code               | GTSNW/120  |
| Range                    | MultiTrack |
| Third party certified    | CE<br>UKCA |
| Geotextile product range | MultiTrack |

### Geotextile properties

|                              |              |                       |
|------------------------------|--------------|-----------------------|
| Tensile strength (MD)        | EN ISO 10319 | 70kN/m                |
| Tensile strength (CMD)       | EN ISO 10319 | 70kN/m                |
| Elongation at max load (MD)  | EN ISO 10319 | 70%                   |
| Elongation at max load (CMD) | EN ISO 10319 | 70%                   |
| CBR puncture resistance      | EN ISO 12236 | 11500N                |
| Dynamic cone drop            | EN ISO 13433 | 0mm                   |
| Water permeability           | EN ISO 11058 | 20L/m <sup>2</sup> .s |

## NOTES

Product may be subject to longer lead times, contact the Wrekin Geosynthetics team for details.

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

