

DBTOA4/1515/KT (discontinued)

Tristar Grade A surface box 150mm x 150mm clear opening with 100mm frame depth



SUPERSEDED BY

Stock code	Range	Clear opening (mm)	Overall frame (mm)	Frame depth (mm)
DBT0A4/1515	Tristar	150 x 150	230 x 230	100

CHARACTERISTIC	VALUE
Range	Tristar
Clear opening (mm)	150 x 150
Overall frame (mm)	250 x 250
Frame depth (mm)	100

SPECIFICATION

GENERAL INFORMATION

DBT0A4/1515/KT	
Ductile iron	
Tristar	
Surface box	
4	
	Ductile iron Tristar

STANDARDS, CLASSES AND GROUPINGS

Standards	BS5834	
BS 5834 Grade	Α	

DIMENSIONS

Frame shape	Square	
Manhole shape	Square	
Overall frame (A x B)	250 mm x 250 mm	
Clear opening (C x D)	150 mm x 150 mm	
Frame depth (E)	100mm	
Base opening (F x G)	170 mm x 170 mm	

EPD DATA

Total life cycle (cradle to grave) 13.92 kg CO₂ equivalent



Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U6.5	6.5Kg Unipak® rapid curing polyester resin mortar
KEYSLIGHT	Small cover lifting keys with a standard handle (sold as a pair)

- ► All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- Where errors or omissions are identified, amendments will be made as quickly as possible.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our terms and conditions of sale.



