


DBTOA4/1515/KT (discontinued)

Tristar Grade A surface box 150mm x 150mm clear opening with 100mm frame depth



SUPERSEDED BY

Stock code	Range	Clear opening (mm)	Overall frame (mm)	Frame depth (mm)
DBTOA4/1515	Tristar	150 x 150	230 x 230	100

CHARACTERISTIC	VALUE
Range	Tristar
Clear opening (mm)	150 x 150
Overall frame (mm)	250 x 250
Frame depth (mm)	100

SPECIFICATION

GENERAL INFORMATION

Stock code	DBTOA4/1515/KT
Primary material	Ductile iron
Range	Tristar
Category	Surface box
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS5834
BS 5834 Grade	A

DIMENSIONS

Frame shape	Square
Manhole shape	Square
Overall frame (A x B)	250 mm x 250 mm
Clear opening (C x D)	150 mm x 150 mm
Frame depth (E)	100mm
Base opening (F x G)	170 mm x 170 mm

EPD DATA

Total life cycle (cradle to grave) 13.92 kg CO₂ equivalent



ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U6.5	6.5Kg Unipak® rapid curing polyester resin mortar
KEYSLIGHT	Small cover lifting keys with a standard handle (sold as a pair)

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).