



DMTOE6/1268/KP4

Pulse E600 manhole cover 1,220mm x 680mm clear opening with 150mm frame depth - 4 padlock points (padlocks not included).



CHARACTERISTIC	VALUE
Range	Pulse
Clear opening (mm)	1,220 x 680
Overall frame (mm)	1,325 x 940
Frame depth (mm)	150
Options	▶ Enhanced anti-slip coating ▶ ID and comms badging ▶ Standard badging ▶ Pressure relief holes



SPECIFICATION

GENERAL INFORMATION

Stock code	DMTOE6/1268/KP4
Primary material	Ductile iron
Range	Pulse
Category	Manhole cover
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2 DMRB MCHW CD 534 v0.2.0
BS EN 124 Class	E600
BS EN 124 Group	5
Third party certified	Kitemark

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	1,325 mm x 940 mm
Clear opening (C x D)	1,220 mm x 680 mm
Frame depth (E)	150mm
Base opening (F x G)	1,220 mm x 680 mm

FEATURES

- ✓ Non-rocking three-point suspension provides stable seating for silent, reliable operation.
- ✓ Independently tested by a UKAS-accredited laboratory to achieve a PSRV value of 70+ on the chequer surface.
- ✓ Enlarged corners spread loads evenly across the foundation, enhancing reliability and lifespan.
- ✓ Gussets dissipate loading stresses effectively, providing long-term durability by preventing damage to the frame and bedding material.
- ✓ Built-in lifting points allow safe mechanical lifting, reducing manual handling and improving on-site safety.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach.
- ✓ Optional ID badge supports RFID, NFC and IoT connectivity for asset identification and tracking.
- ✓ Safety keyways prevent accidental lifting key disengagement during handling for safer operation.
- ✓ Texturing above and below the flange improves mortar grip and reduces lateral movement and cracking.
- ✓ I-beam structure increases rigidity and reduces seat wear for a longer service life.
- ✓ Meets the requirements of CD 534 v0.2.0.

AVAILABLE OPTIONS

- ✓ **Enhanced anti-slip coating**
An enhanced anti-slip coating provides increased anti-slip protection as an addition to the product's own anti-skid properties.
- ✓ **ID badging and communications options**
Bespoke badging and communications antennae, including NFC, RFID and IoT technology.
- ✓ **Industry standard badging**
Integral industry-standard badging e.g. SW (Storm Water) and FW (Foul Water). Details are taken at point of order.
- ✓ **Pressure relief holes**
Pressure relief holes provide additional airflow, with sizes permitted up to the maximum allowances specified in BS EN 124.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak [®] rapid curing polyester resin mortar

EPD DATA

Total life cycle (cradle to grave) 565.15 kg CO₂ equivalent



STOCK CODE	DESCRIPTION
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar
KEYS/HEAVY	Large cover lifting keys with a standard handle
KEYS/LONG	Large cover lifting keys with a long handle
KEYS/L	Small cover combined lifting key
SCREWLIFT	Simple and rapid manhole frame levelling system. Simply push the bushes into the holes in the flange and adjust the levelling screws to the required height.

- All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- Where errors or omissions are identified, amendments will be made as quickly as possible.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the [knowledge base](#).
- All Wrekin products are supplied subject to our [terms and conditions of sale](#).