


C211 N/060060PSF

Pressed Steel Access Cover, 600mm x 600mm clear opening,
25mm depth, Loading code N



| CHARACTERISTIC | VALUE |
|---------------------------|-------------|
| Clear opening (mm) | 600 x 600 |
| Overall top of frame (mm) | 625 x 625 |
| Frame depth (mm) | 25 |
| Load duty | Medium duty |

SPECIFICATION

GENERAL INFORMATION

| | |
|---|-----------------|
| Stock code | C211N/060060PSF |
| Primary material | Steel |
| Category | Access cover |
| Flanges | 4 |
| Gross laden vehicle weight | 25 tn |
| Load duty | Medium duty |
| Slow moving wheel load (pneumatic tyres) | 5 tn |
| Seal type | Single seal |

STANDARDS, CLASSES AND GROUPINGS

| | |
|---------------------|---|
| Wrekin loading code | N |
|---------------------|---|

DIMENSIONS

| | |
|------------------------------|-----------------|
| Frame shape | Rectangular |
| Overall top of frame (A x B) | 625 mm x 625 mm |
| Clear opening (C x D) | 600 mm x 600 mm |
| Frame depth (E) | 25mm |

FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Keyway lifting points are provided on the frame for safe handling.

- ✓ Lifting handle

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).

