

## C233N/091044/BT

Recessed cover for block paving, 915mm x 445mm clear opening, 86mm frame depth, Wrekin loading code N, BT Approved



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
915 x 445	980 x 520	86	

## FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Can be installed by a single person, providing labour cost savings.

## SPECIFICATION

### General information

Stock code	C233N/091044/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3
Chamber ref	4

## Standards, classes and groupings

<b>BS EN 124 Class</b>	B125
<b>Wrekin loading code</b>	N

## Dimensions

<b>Frame shape</b>	Rectangular
<b>Overall frame (A x B)</b>	
<b>Overall top of frame (A x B)</b>	520 mm x 980 mm
<b>Clear opening (C x D)</b>	915 mm x 445 mm
<b>Frame depth (E)</b>	86mm
<b>Base opening (F x G)</b>	
<b>Overall base of frame</b>	605 mm x 1,075 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

