



### C271M/030030

Steel Recessed Access Cover, double seal and locked, 300mm x 300mm clear opening, 38mm frame depth, 58mm frame depth, Loading code M  $\,$ 



CHARACTERISTIC	VALUE
Clear opening (mm)	300 x 300
Overall top of frame (mm)	385 x 385
Frame depth (mm)	58
Load duty	Light / medium duty



## **SPECIFICATION**

### **GENERAL INFORMATION**

Stock code	C271M/030030
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	
Seal type	Double seal

#### **STANDARDS, CLASSES AND GROUPINGS**

DIMENSIONS		
Frame shape	Rectangular	
Overall top of frame (A x B)	385 mm x 385 mm	
Clear opening (C x D)	300 mm x 300 mm	
Frame depth (E)	58mm	
Overall base of frame	380 mm x 380 mm	

Μ

## **FEATURES**

Hot-dipped galvanised to provide long-lasting corrosion resistance for extended service life.

# **ACCESSORIES**

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code





STOCK CODE	DESCRIPTION
KEYSRECESSED	Recessed cover lifting keys (sold as a pair)

### **NOTES**

Full loading capability is achieved when fully filled with grade C25 concrete

Mild steel - Galvanised to BS EN ISO 1461

Locking screws - Countersunk, slotted, M8 x 45 mm long

Unlocking - Flathead screwdriver

Lifting keys - Wire J-shaped key (Wrekin product code KEYSRECESSED)

The vertical top edge of the cover will accept up to a 12 mm tile

- ▶ All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- ▶ Where errors or omissions are identified, amendments will be made as quickly as possible.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our terms and conditions of sale.





