



C271M/090060

Steel Recessed Access Cover, double seal and locked, 900mm $\rm x$ 600mm clear opening, 58mm tray depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	900 x 600
Overall top of frame (mm)	985 x 685
Frame depth (mm)	58
Load duty	Light / medium duty



SPECIFICATION

GENERAL INFORMATION

Stock code	C271M/090060
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	
Seal type	Double seal

STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	М
DIMENSIONS	
Frame shape	Rectangular
Overall top of frame (A x B)	685 mm x 985 mm

58mm

900 mm x 600 mm

FEATURES

Hot-dipped galvanised to provide long-lasting corrosion resistance for extended service life.

ACCESSORIES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Clear opening (C x D)

Frame depth (E)





STOCK CODE	DESCRIPTION
KEYSRECESSED	Recessed cover lifting keys (sold as a pair)

NOTES

Full loading capability is achieved when fully filled with grade C25 concrete

Mild steel - Galvanised to BS EN ISO 1461

Locking screws - Countersunk, slotted, M8 x 45 mm long

Unlocking - Flathead screwdriver

Lifting keys - Wire J-shaped key (Wrekin product code KEYSRECESSED)

The vertical top edge of the cover will accept up to a 12 mm tile

- ▶ All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- ▶ Where errors or omissions are identified, amendments will be made as quickly as possible.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our terms and conditions of sale.





