


C281M/060060

Steel Recessed Access Cover, 600mm x 600mm clear opening, 80mm tray depth, 85mm frame depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 600
Overall top of frame (mm)	640 x 640
Frame depth (mm)	85
Load duty	Light / medium duty



SPECIFICATION

GENERAL INFORMATION

Stock code	C281M/060060
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	

STANDARDS, CLASSES AND GROUPINGS

DIMENSIONS		
Frame shape	Rectangular	
Overall top of frame (A x B)	640 mm x 640 mm	
Clear opening (C x D)	600 mm x 600 mm	
Frame depth (E)	85mm	
Overall base of frame	740 mm x 640 mm	

М

FEATURES

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

NOTES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code





Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)

- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the $\underline{\text{knowledge base}}$.
- All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 in fo@wrekin products.comwrekinproducts.com





