


# C281M/060060

Steel Recessed Access Cover, 600mm x 600mm clear opening, 80mm tray depth, 85mm frame depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 600
Overall top of frame (mm)	640 x 640
Frame depth (mm)	85
Load duty	Light / medium duty



# **SPECIFICATION**

### **GENERAL INFORMATION**

Stock code	C281M/060060
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	

#### **STANDARDS, CLASSES AND GROUPINGS**

DIMENSIONS	
Frame shape	Rectangular
Overall top of frame (A x B)	640 mm x 640 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	85mm
Overall base of frame	740 mm x 640 mm

М

# **FEATURES**

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

# **NOTES**

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code





Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





