


C281M/075060

Steel Recessed Access Cover, 750mm x 600mm clear opening, 80mm tray depth, 85mm frame depth, Loading code M $\,$



CHARACTERISTIC	VALUE
Clear opening (mm)	750 x 600
Overall top of frame (mm)	790 x 640
Frame depth (mm)	85
Load duty	Light / medium duty



SPECIFICATION

GENERAL INFORMATION

C281M/075060
Steel
Access cover
4
10 tn
Light / medium duty
2.5

STANDARDS, CLASSES AND GROUPINGS

DIMENSIONS	
Frame shape	Rectangular
Overall top of frame (A x B)	640 mm x 790 mm
Clear opening (C x D)	750 mm x 600 mm
Frame depth (E)	85mm

750 mm x 790 mm

Μ

FEATURES

Hot-dipped galvanised to provide long-lasting corrosion resistance for extended service life. Integrated keyway frame lifting points provide safe and secure handling.

NOTES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code

Overall base of frame





Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)

- All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- ▶ Where errors or omissions are identified, amendments will be made as quickly as possible.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- Installation details are available in the knowledge base.
- All Wrekin products are supplied subject to our terms and conditions of sale.





