


## C291M/045045

Steel Recessed Access Cover, 450mm x 450mm clear opening, 100mm tray depth, Loading code  $\rm M$ 



CHARACTERISTIC	VALUE
Clear opening (mm)	450 x 450
Overall top of frame (mm)	490 x 490
Frame depth (mm)	105
Load duty	Light / medium duty



# **SPECIFICATION**

### **GENERAL INFORMATION**

Stock code	C291M/045045
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	

#### **STANDARDS, CLASSES AND GROUPINGS**

DIMENSIONS		
Frame shape	Rectangular	
Overall top of frame (A x B)	490 mm x 490 mm	
Clear opening (C x D)	450 mm x 450 mm	
Frame depth (E)	105mm	
Overall base of frame	580 mm x 490 mm	

М

## **FEATURES**

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

## **NOTES**

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code





Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)

- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the  $\underline{\text{knowledge base}}$ .
- All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 in fo@wrekin products.comwrekinproducts.com





