


C291M/067067

Steel Recessed Access Cover, 675mm x 675mm clear opening, 100mm tray depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	675 x 675
Overall top of frame (mm)	715 x 715
Frame depth (mm)	105
Load duty	Light / medium duty



SPECIFICATION

GENERAL INFORMATION

Stock code	C291M/067067
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	

STANDARDS, CLASSES AND GROUPINGS

DIMENSIONS		
Frame shape	Rectangular	
Overall top of frame (A x B)	715 mm x 715 mm	
Clear opening (C x D)	675 mm x 675 mm	
Frame depth (E)	105mm	
Overall base of frame	815 mm x 715 mm	

Μ

FEATURES

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

NOTES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code





Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ► All values stated are nominal within 2.5% tolerance.
- \blacktriangleright Installation details are available in the <u>knowledge base</u>.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale.</u>





