

C221K/060045PSF

Double Seal Pressed Steel Access Cover, $600 \text{mm} \times 450 \text{mm}$ clear opening, 25 mm depth, Loading code K



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 450
Overall top of frame (mm)	630 x 480
Frame depth (mm)	25
Load duty	Pedestrian

SPECIFICATION

GENERAL INFORMATION

Stock code	C221K/060045PSF	
Primary material	Steel	
Category	Access cover	
Flanges	4	
Gross laden vehicle weight	2.5 tn	
Load duty	Pedestrian	
Seal type	Double seal	

STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	K	

DIMENSIONS

Frame shape	Rectangular
Overall top of frame (A x B)	480 mm x 630 mm
Clear opening (C x D)	600 mm x 450 mm
Frame depth (E)	25mm

FEATURES

- Hot dipped galvanised for corrosion resistance.
- Lifting handle

Keyway lifting points are provided on the frame for safe handling.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale.</u>

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





