

C221K/060060PSF

Double Seal Pressed Steel Access Cover, 600mm x 600mm clear opening, 25mm depth, Loading code K



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	630 x 630	25	Pedestrian

FEATURES

→ Hot dipped galvanised for corrosion resistance.

Lifting handle

Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code C221K/060060PSF

Primary material Steel

Category Access cover

Flanges 4

Gross laden vehicle weight 2.5 tn

Load duty Pedestrian

Seal type Double seal





Standards, classes and groupings

Wrekin loading code K

Dimensions

Frame shape Rectangular

Overall top of frame (A x B) 630 mm x 630 mm

Clear opening (C x D) 600 mm x 600 mm

Frame depth (E) 25mm

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the knowledge base.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







