

C221L/060045PSF

Double Seal Pressed Steel Access Cover, 600mm x 450mm clear opening, 25mm depth, Loading code L



| CLEAR OPENING (MM) | OVERALL TOP OF FRAME (MM) | FRAME DEPTH (MM) | LOAD DUTY |
|--------------------|---------------------------|------------------|---------------------|
| 600 x 450 | 630 x 480 | 25 | Domestic light duty |

FEATURES

→ Hot dipped galvanised for corrosion resistance.

Lifting handle

Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code C221L/060045PSF

Primary material Steel

Category Access cover

Flanges 4

Gross laden vehicle weight 5 tn

Load duty Domestic light duty

Slow moving wheel load (pneumatic tyres) 1.25 tn

Seal type Double seal





Standards, classes and groupings

Wrekin loading code

Dimensions

Frame shape Rectangular

Overall top of frame (A x B) 630 mm x 480 mm

Clear opening (C x D) 600 mm x 450 mm

Frame depth (E) 25mm

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the knowledge base.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







