


C221L/060045PSF

Double Seal Pressed Steel Access Cover, $600 \text{mm} \times 450 \text{mm}$ clear opening, 25 mm depth, Loading code L



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 450
Overall top of frame (mm)	630 x 480
Frame depth (mm)	25
Load duty	Domestic light duty

SPECIFICATION

GENERAL INFORMATION

Stock code	C221L/060045PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	5 tn
Load duty	Domestic light duty
Slow moving wheel load	1.25 tn
(pneumatic tyres)	
Seal type	Double seal

STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	L	

DIMENSIONS

Frame shape	Rectangular
Overall top of frame (A x B)	480 mm x 630 mm
Clear opening (C x D)	600 mm x 450 mm
Frame depth (E)	25mm

FEATURES

- Provides long-lasting corrosion resistance for extended service life.
- __ Lifting handle

Integrated keyway frame lifting points provide safe and secure handling.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale.</u>

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





