

## C261N/170071/BT

BT Approved Steel Recessed Access Cover, 1705mm x 710mm clear opening, 43mm tray depth, 46mm frame depth, Loading code N

| CLEAR OPENING<br>(MM) | OVERALL TOP OF FRAME<br>(MM) | FRAME DEPTH<br>(MM) | LOAD DUTY |
|-----------------------|------------------------------|---------------------|-----------|
| 1,705 x 710           |                              | 46                  |           |

## FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.

## SPECIFICATION

### General information

|                  |                 |
|------------------|-----------------|
| Stock code       | C261N/170071/BT |
| Primary material | Steel           |
| Category         | Access cover    |
| Flanges          | 4               |
| Number of lids   | 3               |

### Standards, classes and groupings

|                     |      |
|---------------------|------|
| BS EN 124 Class     | B125 |
| Wrekin loading code | N    |

## Dimensions

|                              |                   |
|------------------------------|-------------------|
| <b>Frame shape</b>           | Rectangular       |
| <b>Clear opening (C x D)</b> | 1,705 mm x 710 mm |
| <b>Frame depth (E)</b>       | 46mm              |
| <b>Overall base of frame</b> | 802 mm x 1,797 mm |

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

