

### C261N/170071/BT

BT Approved Steel Recessed Access Cover, 1705mm x 710mm clear opening, 43mm tray depth, 46mm frame depth, Loading code N  $\,$ 

CHARACTERISTIC	VALUE
Clear opening (mm)	1,705 x 710
Overall top of frame (mm)	
Frame depth (mm)	46
Load duty	

# **SPECIFICATION**

#### **GENERAL INFORMATION**

Stock code	C261N/170071/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3

## STANDARDS, CLASSES AND GROUPINGS

BS EN 124 Class	B125
Wrekin loading code	N

#### **DIMENSIONS**

Frame shape	Rectangular
Clear opening (C x D)	1,705 mm x 710 mm
Frame depth (E)	46mm
Overall base of frame	802 mm x 1,797 mm

## **FEATURES**

- Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- Hot dipped galvanised for corrosion resistance.
- Covers have been approved for use by telecommunications companies such as Openreach.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the <u>knowledge base</u>.

  All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





