

C261N/232074/BT

BT Approved Steel Recessed Access Cover, 2319mm x 742mm clear opening, 43mm tray depth, 46mm frame depth, Loading code N

CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
2,319 x 742		46	

FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.

SPECIFICATION

General information

Stock code	C261N/232074/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3

Standards, classes and groupings

BS EN 124 Class	B125
Wrekin loading code	N

Dimensions

Frame shape	Rectangular
Overall frame (A x B)	
Clear opening (C x D)	2,319 mm x 742 mm
Frame depth (E)	46mm
Base opening (F x G)	
Overall base of frame	834 mm x 2,411 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

