

C261N/232074/BT

BT Approved Steel Recessed Access Cover, 2319mm x 742mm clear opening, 43mm tray depth, 46mm frame depth, Loading code N

CHARACTERISTIC	VALUE
Clear opening (mm)	2,319 x 742
Overall top of frame (mm)	
Frame depth (mm)	46
Load duty	

SPECIFICATION

GENERAL INFORMATION

Stock code	C261N/232074/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3

STANDARDS, CLASSES AND GROUPINGS

BS EN 124 Class	B125
Wrekin loading code	N

DIMENSIONS

Frame shape	Rectangular
Clear opening (C x D)	2,319 mm x 742 mm
Frame depth (E)	46mm
Overall base of frame	834 mm x 2,411 mm

FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach.

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).

