

CALPRO80N/090060 (discontinued)


Aluminium Recessed Access Cover, 900mm x 600mm clear opening, 65mm tray depth, 80mm frame depth, Loading code N



SUPERSEDED BY

| Stock code | Clear opening (mm) | Overall top of frame (mm) | Frame depth (mm) | Load duty |
|------------------|--------------------|---------------------------|------------------|-------------|
| CALPRO60N/090060 | 900 x 600 | 990 x 690 | 60 | Medium duty |

| CHARACTERISTIC | VALUE |
|---------------------------|-------------|
| Clear opening (mm) | 900 x 600 |
| Overall top of frame (mm) | 990 x 690 |
| Frame depth (mm) | 80 |
| Load duty | Medium duty |



SPECIFICATION

GENERAL INFORMATION

| Stock code | CALPRO80N/090060 | |
|----------------------------|------------------|--|
| Primary material | Aluminium | |
| Category | Access cover | |
| Flanges | 4 | |
| Gross laden vehicle weight | 25 tn | |
| Load duty | Medium duty | |
| Slow moving wheel load | 5 tn | |
| (pneumatic tyres) | | |
| Seal type | Triple seal | |

STANDARDS, CLASSES AND GROUPINGS

| N | |
|-----------------|--|
| | |
| | |
| 690 mm x 990 mm | |
| 900 mm x 600 mm | |
| 80mm | |
| | |

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale.</u>

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





