


C221M/060060PSF

Double Seal Pressed Steel Access Cover, $600 \text{mm} \times 600 \text{mm}$ clear opening, 25 mm depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 600
Overall top of frame (mm)	630 x 630
Frame depth (mm)	25
Load duty	Light / medium duty

SPECIFICATION

GENERAL INFORMATION

Clark and	000114/000000000
Stock code	C221M/060060PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	
Seal type	Double seal

STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	М	

DIMENSIONS

Frame shape	Rectangular
Overall top of frame (A x B)	630 mm x 630 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	25mm

FEATURES

- Hot dipped galvanised for corrosion resistance.
- Lifting handle

Keyway lifting points are provided on the frame for safe handling.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms</u> and <u>Conditions of Sale.</u>

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





