


C221M/060060PSF

Double Seal Pressed Steel Access Cover, 600mm x 600mm clear opening, 25mm depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	630 x 630	25	Light / medium duty

FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Lifting handle
- ✓ Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code	C221M/060060PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal

Standards, classes and groupings

Wrekin loading code M

Dimensions

Frame shape	Rectangular
Overall top of frame (A x B)	630 mm x 630 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	25mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

