

# C221M/060060PSF

Double Seal Pressed Steel Access Cover,  $600 \text{mm} \times 600 \text{mm}$  clear opening, 25 mm depth, Loading code M



CHARACTERISTIC	VALUE
Clear opening (mm)	600 x 600
Overall top of frame (mm)	630 x 630
Frame depth (mm)	25
Load duty	Light / medium duty

# **SPECIFICATION**

#### **GENERAL INFORMATION**

Stock code	C221M/060060PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	
Seal type	Double seal

## STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	М	

## **DIMENSIONS**

Frame shape	Rectangular
Overall top of frame (A x B)	630 mm x 630 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	25mm

# **FEATURES**

- Hot dipped galvanised for corrosion resistance.
- Lifting handle

Keyway lifting points are provided on the frame for safe handling.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the <u>knowledge base</u>.

  All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





