

C291N/067067

Steel Block Paviour Access Cover, 675mm x 675mm clear opening, 100mm tray depth, Loading code N

CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
675 x 675	740 x 740	105	Heavy duty

FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code	C291N/067067
Primary material	Steel
Category	Access cover
Gross laden vehicle weight	25 tn
Load duty	Heavy duty
Slow moving wheel load (pneumatic tyres)	5 tn

Standards, classes and groupings

Wrekin loading code	N
---------------------	---

Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	
Overall top of frame (A x B)	740 mm x 740 mm
Clear opening (C x D)	675 mm x 675 mm
Frame depth (E)	105mm
Base opening (F x G)	
Overall base of frame	825 mm x 740 mm

NOTES

Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy duty key (product code KEYSHEAVY)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

