

## DGK115/HB/K (discontinued)

D400 4 flange kerb unit 495mm x 345mm clear opening with 150mm frame depth



## SUPERSEDED BY

Stock code	Range	Clear opening (mm)	Overall frame (mm)	Frame depth (mm)
DGK115/HB/KG	H2GO	440 x 305	645 x 445	150

CHARACTERISTIC	VALUE
Range	
Clear opening (mm)	495 x 345
Overall frame (mm)	645 x 445
Frame depth (mm)	150
Options	► Screw locking

## SPECIFICATION

### GENERAL INFORMATION

Stock code	DGK115/HB/K
Primary material	Ductile iron
Category	Kerb unit
Flanges	4

### STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
BS EN 124 Class	D400
BS EN 124 Group	3
Third party certified	Kitemark

### DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	645 mm x 445 mm
Clear opening (C x D)	495 mm x 345 mm
Frame depth (E)	150mm
Base opening (F x G)	530 mm x 365 mm

### EPD DATA

Total life cycle (cradle to grave) 103.92 kg CO<sub>2</sub> equivalent



## FEATURES

- ✓ Captive hinges reduce theft risk whilst allowing easy lifting.

## AVAILABLE OPTIONS

- ✓ **Screw locking**  
Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).