

DGK115/HB/K (discontinued)

D400 4 flange kerb unit 495mm x 345mm clear opening with 150mm frame depth



SUPERSEDED BY

| Stock code | Range | Clear opening (mm) | Overall frame (mm) | Frame depth (mm) |
|--------------|-------|--------------------|-----------------------|------------------|
| DGK115/HB/KG | H2GO | 440 x 305 | 645 x 445 | 150 |

| CHARACTERISTIC | VALUE |
|--------------------|-----------------|
| Range | |
| Clear opening (mm) | 495 x 345 |
| Overall frame (mm) | 645 x 445 |
| Frame depth (mm) | 150 |
| Options | ► Screw locking |

SPECIFICATION

GENERAL INFORMATION

| Stock code | DGK115/HB/K |
|------------------|--------------|
| Primary material | Ductile iron |
| Category | Kerb unit |
| Flanges | 4 |

STANDARDS, CLASSES AND GROUPINGS

| Standards | BS EN 124-2 |
|-----------------------|-------------|
| BS EN 124 Class | D400 |
| BS EN 124 Group | 3 |
| Third party certified | Kitemark |

DIMENSIONS

| Frame shape | Rectangular | |
|-----------------------|-----------------|--|
| Manhole shape | Rectangular | |
| Overall frame (A x B) | 645 mm x 445 mm | |
| Clear opening (C x D) | 495 mm x 345 mm | |
| Frame depth (E) | 150mm | |
| Base opening (F x G) | 530 mm x 365 mm | |

EPD DATA

| Total life cycle (cradle to | 103.92 kg CO2 equivalent | |
|-----------------------------|--------------------------|--|
| grave) | | |



Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







FEATURES

Captive hinges reduce theft risk whilst allowing easy lifting.

AVAILABLE OPTIONS

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

| STOCK CODE | DESCRIPTION |
|--------------------|--|
| PC/UNIFORM/151076 | Uniform chamber adjustment unit 760mm x 100mm x 15mm |
| PC/UNIFORM/251076 | Uniform chamber adjustment unit 760mm x 100mm x 25mm |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm |
| YPCR/U12.5 | 12.5Kg Unipak [®] rapid curing polyester resin mortar |
| YPCR/U25 | 25Kg Unipak [®] rapid curing polyester resin mortar |

- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale.</u>





