


## DMH0D4/1383/K


Vault D400 manhole cover 1300mm x 850mm clear opening with 100mm frame depth



RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	OPTIONS
Vault	1,300 x 850	1,490 x 1,050	100	<input type="checkbox"/> Pressure release holes <input type="checkbox"/> Flood and odour control plate <input type="checkbox"/> Safety grille

## FEATURES

- ✓ The enlarged frame corners help to dissipate loads onto the foundation, providing a longer service life and increased reliability.
- ✓ Features an LPCB Level 3 lock, offering an unrivalled level of high security.
- ✓ Safety-stop hinges prevent covers from falling once opened.
- ✓ Mechanical lifting points are provided.
- ✓ Secured with a turnbuckle lock.
- ✓ Indexed corners ensure correct orientation first time, every time.
- ✓ Safety keyway prevents accidental disengagement of the lifting key during the handling process.
- ✓ Covers open sequentially, with standard BS7903 lifting keys.
- ✓ 70+ PSRV tested at top surface of chequer by UKAS accredited 3rd party.



## SPECIFICATION

### General information

Stock code	DMHOD4/1383/K
Primary material	Ductile iron
Range	Vault
Category	Manhole cover
Flanges	4

### Standards, classes and groupings

Standards	BS EN 124-2 BRE PN111 DMRB MCHW
BS EN 124 Class	D400

**BS EN 124 Group**

4

**Third party certified**

BRE LPCB  
Kitemark

## Dimensions

**Frame shape**

Rectangular

**Manhole shape**

Rectangular

**Overall frame (A x B)**

1,490 mm x 1,050 mm

**Clear opening (C x D)**

1,300 mm x 850 mm

**Frame depth (E)**

100mm

**Base opening (F x G)**

1,325 mm x 875 mm

## AVAILABLE OPTIONS

### ✓ Pressure release holes

Pressure release holes provide additional airflow, with sizes permitted up to the maximum allowances specified in BS EN 124.

### ✓ Safety grille

Safety grilles prevent accidental chamber falls. Available in a variety of configurations; including bars and mesh as drop-in or hinged.

### ✓ Flood and odour control plate

The flood and odour control plate is manufactured from steel and provides resistance to flood-water ingress and the chamber-odour egress.

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak <sup>®</sup> rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak <sup>®</sup> rapid curing polyester resin mortar

STOCK CODE	DESCRIPTION
KEY/MC	Lifting key for turnbuckle lock on our Vault range of covers
KEYS/L	Small cover combined lifting key
KEY/LONG	Large cover lifting keys with a long handle (sold as a pair)
GRITBLOCKER	Anti-blockage keyway insert
SCREWLIFT	Simple and rapid manhole frame levelling system. Simply push the bushes into the holes in the flange and adjust the levelling screws to the required height.

## NOTES

All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

