


# **DBTOA4/3030**

Tristar Grade A surface box 300mm x 300mm clear opening with 100mm frame depth



| CHARACTERISTIC     | VALUE     |
|--------------------|-----------|
| Range              | Tristar   |
| Clear opening (mm) | 300 x 300 |
| Overall frame (mm) | 380 x 380 |
| Frame depth (mm)   | 100       |



## **SPECIFICATION**

### **GENERAL INFORMATION**

| DBT0A4/3030  |
|--------------|
| Ductile iron |
| Tristar      |
| Surface box  |
| 4            |
|              |

## STANDARDS, CLASSES AND GROUPINGS

| Standards       | BS5834 |
|-----------------|--------|
| BS EN 124 Group | 4      |
| BS 5834 Grade   | A      |

### **DIMENSIONS**

| Frame shape           | Rectangular     |
|-----------------------|-----------------|
| Manhole shape         | Rectangular     |
| Overall frame (A x B) | 380 mm x 380 mm |
| Clear opening (C x D) | 300 mm x 300 mm |
| Frame depth (E)       | 100mm           |
| Base opening (F x G)  | 305 mm x 305 mm |

#### **EPD DATA**

Total life cycle (cradle to grave) 47.1 kg CO<sub>2</sub> equivalent



# **ACCESSORIES**

| STOCK CODE        | DESCRIPTION  |
|-------------------|--|
| PC/UNIFORM/151076 | Uniform chamber adjustment unit 760mm x 100mm x 15mm |

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







| STOCK CODE         | DESCRIPTION  |
|--------------------|--|
| PC/UNIFORM/251076  | Uniform chamber adjustment unit 760mm x 100mm x 25mm             |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm                        |
| YPCR/U6.5          | 6.5Kg Unipak® rapid curing polyester resin mortar                |
| KEYSLIGHT          | Small cover lifting keys with a standard handle (sold as a pair) |

- ▶ All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- Where errors or omissions are identified, amendments will be made as quickly as possible.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ► Installation details are available in the <u>knowledge base</u>.
- ▶ All Wrekin products are supplied subject to our terms and conditions of sale.







