


DGHT0D6/6045/KH4F

Highway D400 4 flange gully grate 425mm x 425mm clear opening with 150mm frame depth (made to order)



CHARACTERISTIC	VALUE
Range	Highway
Clear opening (mm)	425 x 425
Base opening (mm)	600 x 450
Overall frame (mm)	775 x 625
Frame depth (mm)	150
Waterway area (cm²)	1,750
Options	► Screw locking



SPECIFICATION

GENERAL INFORMATION

Stock code	DGHT0D6/6045/KH4F
Primary material	Ductile iron
Range	Highway
Category	Gully grate
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
	DMRB
	MCHW
	CD 534 v0.2.0
BS EN 124 Class	D400
BS EN 124 Group	3
	4
Third party certified	Kitemark
CD 526 hydraulic capacity	Q

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	775 mm x 625 mm
Clear opening (C x D)	425 mm x 425 mm
Frame depth (E)	150mm
Base opening (F x G)	600 mm x 450 mm
Waterway area	1,750cm²

EPD DATA

Total life cycle (cradle to grave) 110.55 kg CO₂ equivalent



Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







FEATURES

- Non-rocking three-point suspension provides stable seating for silent, reliable operation.
- Captive hinges deter theft and allow safe, easy lifting during maintenance.
- Enlarged corners spread loads evenly across the foundation, enhancing reliability and lifespan.
- Strengthened corners dissipate loading stresses effectively, providing long-term durability and preventing damage to the frame and cover.

- Integrated keyway frame lifting points provide safe and secure handling.
- Frame holes allow mortar to flow through the flange, creating a strong mechanical bond for added stability.
- Texturing above and below the flange improves mortar grip and reduces lateral movement and cracking.
- Meets the requirements of CD 534 v0.2.0.

AVAILABLE OPTIONS

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar
SCREWLIFT	Simple and rapid manhole frame levelling system. Simply push the bushes into the holes in the flange and adjust the levelling screws to the required height.

NOTES

- ▶ Can be manufactured on request, <u>please contact the sales team</u> for more information.
- ▶ The D400 load capability of these Group 3 products also offers the benefit of making them suitable for exposure to Group 4 traffic types. Where 3-flange D400 Gully Grate assemblies are employed, we recommend that they are installed against a kerb, not in an open highway location.







Tel: 01543 440 440

- All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative
- Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- Where errors or omissions are identified, amendments will be made as quickly as possible.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the knowledge base.
- All Wrekin products are supplied subject to our terms and conditions of sale.







