


DGH0B3/2222/F

Tristar B125 3 flange gully grate 225mm x 225mm clear opening with 65mm frame depth



| CHARACTERISTIC | VALUE |
|---------------------|-----------------|
| Range | Tristar |
| Clear opening (mm) | 225 x 225 |
| Base opening (mm) | 225 x 225 |
| Overall frame (mm) | 280 x 265 |
| Frame depth (mm) | 65 |
| Waterway area (cm²) | 210 |
| Options | ► Screw locking |



SPECIFICATION

GENERAL INFORMATION

| Stock code | DGH0B3/2222/F |
|------------------|---------------|
| Primary material | Ductile iron |
| Range | Tristar |
| Category | Gully grate |
| Flanges | 3 |

STANDARDS, CLASSES AND GROUPINGS

| - | DO EN 40.4 O |
|---------------------------|--------------|
| Standards | BS EN 124-2 |
| BS EN 124 Class | B125 |
| BS EN 124 Group | 2 |
| Third party certified | Kitemark |
| CD 526 hydraulic capacity | Out of Range |

DIMENSIONS

| Frame shape | Rectangular |
|-----------------------|--------------------|
| Manhole shape | Rectangular |
| Overall frame (A x B) | 280 mm x 265 mm |
| Clear opening (C x D) | 225 mm x 225 mm |
| Frame depth (E) | 65mm |
| Base opening (F x G) | 225 mm x 225 mm |
| Waterway area | 210cm ² |

EPD DATA

Total life cycle (cradle to grave) 18.79 kg CO₂ equivalent



FEATURES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







Captive hinges reduce theft risk whilst allowing easy lifting.

AVAILABLE OPTIONS

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

| STOCK CODE | DESCRIPTION |
|--------------------|--|
| PC/UNIFORM/151076 | Uniform chamber adjustment unit 760mm x 100mm x 15mm |
| PC/UNIFORM/251076 | Uniform chamber adjustment unit 760mm x 100mm x 25mm |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm |
| YPCR/U12.5 | 12.5Kg Unipak® rapid curing polyester resin mortar |
| YPCR/U25 | 25Kg Unipak® rapid curing polyester resin mortar |

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale.</u>



