

DGHOB3/3030/F


Tristar B125 3 flange gully grate 300mm x 300mm clear opening with 75mm frame depth



RANGE	CLEAR OPENING (MM)	BASE OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	WATERWAY AREA (CM <sup>2</sup> )	OPTIONS
Tristar	300 x 300	300 x 300	355 x 345	75	375	<input type="checkbox"/> Screw locking

FEATURES

✓ Captive hinges reduce theft risk whilst allowing easy lifting.





# SPECIFICATION

## General information

Stock code	DGH0B3/3030/F
Primary material	Ductile iron
Range	Tristar
Category	Gully grate
Flanges	3

## Standards, classes and groupings

Standards	BS EN 124-2
BS EN 124 Class	B125
BS EN 124 Group	2
Third party certified	Kitemark
CD 526 hydraulic capacity	Out of Range

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	355 mm x 345 mm
Clear opening (C x D)	300 mm x 300 mm
Frame depth (E)	75mm
Base opening (F x G)	300 mm x 300 mm
Waterway area	375cm <sup>2</sup>



## AVAILABLE OPTIONS

### ✓ Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

## NOTES

All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)