


# **DGH0C3/3333/K**

Tristar C250 3 flange gully grate 335mm x 330mm clear opening with 75mm frame depth



CHARACTERISTIC	VALUE
Range	Tristar
Clear opening (mm)	335 x 330
Base opening (mm)	355 x 350
Overall frame (mm)	480 x 420
Frame depth (mm)	75
Waterway area (cm²)	825
Options	► Screw locking



## **SPECIFICATION**

#### **GENERAL INFORMATION**

Stock code	DGH0C3/3333/K
Primary material	Ductile iron
Range	Tristar
Category	Gully grate
Flanges	3

## STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
	CD 526 (formerly HA 102/17)
BS EN 124 Class	C250
BS EN 124 Group	3
Third party certified	Kitemark
CD 526 hydraulic capacity	S

#### **DIMENSIONS**

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	480 mm x 420 mm
Clear opening (C x D)	335 mm x 330 mm
Frame depth (E)	75mm
Base opening (F x G)	355 mm x 350 mm
Waterway area	825cm²

## **EPD DATA**

Total life cycle (cradle to grave) 27.64 kg CO<sub>2</sub> equivalent



## **FEATURES**

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- Captive hinges deter theft and allow safe, easy lifting during maintenance.
- Allows the grating to hinge in the direction of traffic flow, improving safety during access.

#### **AVAILABLE OPTIONS**

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

## **ACCESSORIES**

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

- ▶ All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- ▶ Where errors or omissions are identified, amendments will be made as quickly as possible.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- All Wrekin products are supplied subject to our terms and conditions of sale.



