

DGH0C3/3333/K

Tristar C250 3 flange gully grate 335mm x 330mm clear opening with 75mm frame depth




RANGE	CLEAR OPENING (MM)	BASE OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	WATERWAY AREA (CM ²)	OPTIONS
Tristar	335 x 330	355 x 350	480 x 420	75	825	<input type="checkbox"/> Screw locking

FEATURES

✓ Captive hinges reduce theft risk whilst allowing easy lifting.

✓ Reversible hinge allows the grating to hinge with the direction of the traffic flow, improving safety.



SPECIFICATION

General information

Stock code	DGH0C3/3333/K
Primary material	Ductile iron
Range	Tristar
Category	Gully grate
Flanges	3

Standards, classes and groupings

Standards	BS EN 124-2 CD 526 (formerly HA 102/17)
BS EN 124 Class	C250
BS EN 124 Group	3
Third party certified	Kitemark
CD 526 hydraulic capacity	S

Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	480 mm x 420 mm
Clear opening (C x D)	335 mm x 330 mm
Frame depth (E)	75mm
Base opening (F x G)	355 mm x 350 mm
Waterway area	825cm ²

AVAILABLE OPTIONS

✓ Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak [®] rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak [®] rapid curing polyester resin mortar

NOTES

All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

