


DGH0C3/3832/K1

Tristar C250 3 flange gully grate $385 \text{mm} \times 320 \text{mm}$ clear opening with 75 mm frame depth, locked as standard



CHARACTERISTIC	VALUE
Range	Tristar
Clear opening (mm)	385 x 320
Base opening (mm)	410 x 350
Overall frame (mm)	545 x 425
Frame depth (mm)	75
Waterway area (cm²)	735



SPECIFICATION

GENERAL INFORMATION

Stock code	DGH0C3/3832/K1
Primary material	Ductile iron
Range	Tristar
Category	Gully grate
Flanges	3

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2 CD 526 (formerly HA 102/17)
BS EN 124 Class	C250
BS EN 124 Group	3
Third party certified	Kitemark
CD 526 hydraulic capacity	S

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	545 mm x 425 mm
Clear opening (C x D)	385 mm x 320 mm
Frame depth (E)	75mm
Base opening (F x G)	410 mm x 350 mm
Waterway area	735cm²

EPD DATA

Total life cycle (cradle to grave) 48.65 kg CO₂ equivalent



FEATURES

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







- Captive hinges deter theft and allow safe, easy lifting during maintenance.
- Smaller openings increase safety for pedestrians and cyclists compared with standard gratings.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar

NOTES

This product is locked as standard. The locking bolt can be removed with a 14mm hex key.

- All information provided is subject to change without notice. While every effort is made to ensure accuracy and relevance, Wrekin Products Ltd. does not warrant the completeness or reliability of the information contained herein. Photographs, illustrations, and other visual materials are provided for illustrative purposes only.
- ▶ Wrekin Products Ltd. reserves the right to make design amendments or improvements to any product at any time, where such changes enhance performance or durability, without affecting compliance with the stated standards.
- Where errors or omissions are identified, amendments will be made as quickly as possible.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our terms and conditions of sale.





