

DMH0D8/1267/M1

D400 MC&F 1220 x 675 x 195 Hinged Floating Frame, badged Cubis

| RANGE | CLEAR OPENING (MM) | OVERALL FRAME (MM) | FRAME DEPTH (MM) | OPTIONS |
|-------|-----------------------|--------------------|------------------|---------------|
| | 1,195 x 650 | 1,450 x 895 | 190 | Screw locking |

FEATURES

- Features an LPCB Level 3 lock, offering an unrivalled level of high security.
- Safety-stop hinges prevent covers from falling once opened.
- Safety keyway prevents accidental disengagement of the lifting key during the handling process.
- Covers open sequentially, with standard BS7903 lifting keys.

SPECIFICATION

General information

Stock code DMH0D8/1267/M1

Primary material Ductile iron

Category Manhole cover

Flanges

Standards, classes and groupings

Standards BS EN 124-2

BS EN 124 Class D400

BS EN 124 Group

2

3

4





Third party certified

Kitemark

Dimensions

Frame shape

Rectangular

Manhole shape

Rectangular

Overall frame (A x B)

1,450 mm x 895 mm

Clear opening (C x D)

1,195 mm x 650 mm

Frame depth (E)

190mm

Base opening (F x G)

AVAILABLE OPTIONS

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

| STOCK CODE | DESCRIPTION | |
|--------------------|--|--|
| PC/UNIFORM/151076 | Uniform chamber adjustment unit 760mm x 100mm x 15mm | |
| PC/UNIFORM/251076 | Uniform chamber adjustment unit 760mm x 100mm x 25mm | |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm | |
| YPCR/U12.5 | 12.5Kg Unipak [®] rapid curing polyester resin mortar | |
| YPCR/U25 | 25Kg Unipak [®] rapid curing polyester resin mortar | |
| KEY/LONG | Large cover lifting keys with a long handle (sold as a pair) | |
| KEYS/L | Small cover combined lifting key | |





STOCK CODE

DESCRIPTION

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our Terms and Conditions of Sale







