

DMH0D8/1267/M1

D400 MC&F 1220 x 675 x 195 Hinged Floating Frame, badged Cubis

CHARACTERISTIC	VALUE
Range	
Clear opening (mm)	1,195 x 650
Overall frame (mm)	1,450 x 895
Frame depth (mm)	190
Options	► Screw locking

SPECIFICATION

GENERAL INFORMATION

Stock code	DMH0D8/1267/M1
Primary material	Ductile iron
Category	Manhole cover
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
BS EN 124 Class	D400
BS EN 124 Group	1
	2
	3
	4
Third party certified	Kitemark

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	1,450 mm x 895 mm
Clear opening (C x D)	1,195 mm x 650 mm
Frame depth (E)	190mm

FEATURES

Features an LPCB Level 3 lock, offering an unrivalled high security performance. Safety keyway prevents accidental disengagement of the lifting key during the handling process.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







AVAILABLE OPTIONS

Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar
KEY/LONG	Large cover lifting keys with a long handle (sold as a pair)
KEYS/L	Small cover combined lifting key

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the knowledge base.
- ▶ All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale.</u>



