

## DMHOD8/1267/M1

D400 MC&F 1220 x 675 x 195 Hinged Floating Frame, badged Cubis

| CHARACTERISTIC     | VALUE           |
|--------------------|-----------------|
| Range              |                 |
| Clear opening (mm) | 1,195 x 650     |
| Overall frame (mm) | 1,450 x 895     |
| Frame depth (mm)   | 190             |
| Options            | ► Screw locking |

## SPECIFICATION

### GENERAL INFORMATION

|                  |                |
|------------------|----------------|
| Stock code       | DMHOD8/1267/M1 |
| Primary material | Ductile iron   |
| Category         | Manhole cover  |
| Flanges          | 4              |

### STANDARDS, CLASSES AND GROUPINGS

|                       |                  |
|-----------------------|------------------|
| Standards             | BS EN 124-2      |
| BS EN 124 Class       | D400             |
| BS EN 124 Group       | 1<br>2<br>3<br>4 |
| Third party certified | Kitemark         |

### DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Frame shape           | Rectangular       |
| Manhole shape         | Rectangular       |
| Overall frame (A x B) | 1,450 mm x 895 mm |
| Clear opening (C x D) | 1,195 mm x 650 mm |
| Frame depth (E)       | 190mm             |

## FEATURES

- ✓ Features an LPCB Level 3 lock, offering an unrivalled level of high security.
- ✓ Safety keyway prevents accidental disengagement of the lifting key during the handling process.

✓ Safety-stop hinges prevent covers from falling once opened.

✓ Covers open sequentially, with standard BS7903 lifting keys.

## AVAILABLE OPTIONS

### ✓ Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

## ACCESSORIES

| STOCK CODE         | DESCRIPTION  |
|--------------------|--|
| PC/UNIFORM/151076  | Uniform chamber adjustment unit 760mm x 100mm x 15mm           |
| PC/UNIFORM/251076  | Uniform chamber adjustment unit 760mm x 100mm x 25mm           |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm                      |
| YPCR/U12.5         | 12.5Kg Unipak <sup>®</sup> rapid curing polyester resin mortar |
| YPCR/U25           | 25Kg Unipak <sup>®</sup> rapid curing polyester resin mortar   |
| KEY/LONG           | Large cover lifting keys with a long handle (sold as a pair)   |
| KEYS/L             | Small cover combined lifting key                               |

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).

Tel: 01543 440 440  
Fax: 01543 440 444  
[info@wrekinproducts.com](mailto:info@wrekinproducts.com)  
[wrekinproducts.com](http://wrekinproducts.com)

