

DMHOD8/9161/M1

D400 MC&F 915 x 610 x 195 Hinged Floating Frame, badged Cubis

CHARACTERISTIC	VALUE
Range	
Clear opening (mm)	890 x 585
Overall frame (mm)	1,130 x 840
Frame depth (mm)	190
Options	► Screw locking

SPECIFICATION

GENERAL INFORMATION

Stock code	DMHOD8/9161/M1
Primary material	Ductile iron
Category	Manhole cover
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
BS EN 124 Class	D400
BS EN 124 Group	1 2 3 4
Third party certified	Kitemark

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	1,130 mm x 840 mm
Clear opening (C x D)	890 mm x 585 mm
Frame depth (E)	190mm

FEATURES

- ✓ Features an LPCB Level 3 lock, offering an unrivalled level of high security.
- ✓ Safety keyway prevents accidental disengagement of the lifting key during the handling process.

✓ Safety-stop hinges prevent covers from falling once opened.

✓ Covers open sequentially, with standard BS7903 lifting keys.

AVAILABLE OPTIONS

✓ Screw locking

Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak [®] rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak [®] rapid curing polyester resin mortar
KEY/LONG	Large cover lifting keys with a long handle (sold as a pair)
KEYS/L	Small cover combined lifting key

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).

Tel: 01543 440 440
Fax: 01543 440 444
info@wrekinproducts.com
wrekinproducts.com

